

K-MEMORY

M.2 2280 NVME PCIe Gen 4 SOLID STATE DRIVE



Illustrative images

Upgrade your system with the K-MEMORY M.2 2280 NVME Solid State Drive. The K-MEMORY M.2 2280 NVME PCIe Gen 4 Solid State Drive with 3D NAND Flash is 10X x faster than a Sata SSD, available in capacities up to 4TB and .shock- and vibration-resistant for rugged reliability when used in notebooks and other mobile.

Start your system in seconds.

Specification

Capacity	2TB	1TB	512GB	256GB
Sequential Read / Write (MB/s)	7500/6000	7500/6000	7300/4800	7300/4800
Random 4K Read/Write (K/IOPS)	1000/1000	900/1000	900/1000	900/1000
MTBF	2,000,000 hours	2,000,000 hours	2,000,000 hours	2,000,000 hours
Terabytes Written - TBW* <small>Performance may vary based on SSD capacity, hardware test platform, test software, operating systems, and other system variable</small>	2.0PBW	1.0PBW	512GBPS	256GBPS

- Interface: PCIe Gen 4x4, Compliant with NVME 1.4 register interface and common set. Compliant with PCIe Express 3.1
- Dimension (L x W x H): 22mm x 80mm x 2.2mm
- Weight: 7g
- Warranty: 3 Year
- Compliance CE, FCC, BSMI, C-Tick, VCCI, KCC, RRL, RoHS, China RoHS, WEEE, TUV, UL, IC, Marocco, SATA-IO, UKCA
- Power consumption 0.195W idle / 0.279W avg / 0.642W (MAX) read / 1.535W (MAX) write
- Nand Flash: 3D NAND

- Trim support
- Multistep data
- Device sleep support
- Operating temperature: 0°C-70°C
- Storage temperature: -40°C-85°C
- O/S Supported: Windows® 7* / 8.0* / 8.1 / 10 / 11 (*May require driver)
- Shock resistance: 1,500G/0.5m/sec
- Vibration Operating: 5 gRMS, 10-200 Hz
- Vibration Non operating: 4,9 gRMS, 7-800 Hz
- Error correction: ECC

Warranty: 36 months

With immediate exchange offered directly by local supplier worldwide

INFORMATION PROVIDED IN THIS DOCUMENT PERTAIN TO K-MEMORY - PRODUCTS AND IS SUBJECT TO CHANGE AT ANY TIME

www.k-memory.com support: contact@k-memory.com