

K-MEMORY

SATA SOLID STATE DRIVE



Illustrative image

Upgrade your system with the K-memory Sata Solid state Drive

The K-memory Sata Solid state Drive with 3D NAND Flash is 10x faster than a hard drive, available in capacities up to 2TB and .shock- and vibration-resistant for rugged reliability when used in notebooks and other mobile.

Start your system in seconds.

Specification

Capacity	2TB	1TB	512GB	256GB	128GB
Sequential Read / Write (MB/s)	560 / 500	560 / 500	560 / 500	560 / 500	560 / 500
Random Read / Write (IOPS)	95k/84k	95k/84k	95k/84k	95k/81k	95k/81k
MTBF	2,000,000 hours	2,000,000 hours	2,000,000 hours	2,000,000 hours	1,500,000 hours
Terabytes Written - TBW* <small>Performance may vary based on SSD capacity, hardware test platform, test software, operating systems, and other system variable</small>	1280TB	640TB	320TB	160TB	80TB

- Interface: SATA 3 6 Gb/s
- Form Factor: 2.5"
- Dimension (L x W x H): 100.45 x 69.85 x 7mm
- Weight: 46g / 0.1lb
- Warranty: 3 Year
- Compliance CE, FCC, BSMI, C-Tick, VCCI, KCC, RRL, RoHS, China RoHS, WEEE, TUV, UL, IC, Marocco, SATA-IO, UKCA
- Power consumption 0.195W idle / 0.279W avg / 0.642W (MAX) read / 1.535W (MAX) write
- Error correction: ECC

- Nand Flash: 3D NAND
- Trim support
- Multistep data
- Device sleep support
- Operating temperature: : 0°C-70°C
- Storage temperature: -40°C-85°C
- O/S Supported: Windows® 7* / 8.0* / 8.1 / 10 / 11 (*May require driver)
- Shock resistance: 1,500G/0.5m/sec
- Vibration Operating: 5 gRMS, 10-200 Hz
- Vibration Non operating: 4,9 gRMS, 7-800 Hz

Warranty: 36 months

With immediate exchange offered directly by local supplier worldwide

INFORMATION PROVIDED IN THIS DOCUMENT PERTAIN TO K-MEMORY - PRODUCTS AND IS SUBJECT TO CHANGE AT ANY TIME

www.k-memory.com support: contact@k-memory.com