IX-MEMORY

M.2 2280 NVME PCIe Gen 3

SOLID STATE DRIVE

Upgrade your system with the K-MEMORY M.2 2280 NVME Solid State Drive. The K-MEMORY M.2 2280 NVME PCIe Gen 3 Solid State Drive with 3D NAND Flash is 10X x faster than a Sata SSD, available in capacities up to 1TB and

shock- and vibration-resistant for rugged reliability when used in notebooks and other mobile.

Start your system in seconds.

Specification

Capacity	1TB	960GB	512GB	480GB	256GB	240GB	128GB	120GB
Part Number	KMV/1TB	KMV/ 960GB	KMV/ 512GB	KMV/ 480GB	KMV/ 256GB	KMV/ 240GB	KMV/ 128GB	KMV/ 120GB
Sequential Read / Write (MB/s)	3500/2800	2400/1700	3500/2800	2400/1700	3500/2800	2400/1700	3500/2800	2400/1700
Random 4K Read / Write (k/IOPS)	100/190	96/76	100/190	96/76	100/190	96/76	100/190	96/76
MTBF (milion / hours)	2	1,5	2	1,5	2	1,5	2	1,5
Terabytes Written - TBW* Performance may vary based on SSD capacty, hardware test platform, test software, operating systens, and other system variable	640TB	448TB	320TB	224TB	160ТВ	112ТВ	80ТВ	56TB

- Interface: PCle Gen 3, Compliant with NVME 1.3 register interface and comman set. Compliant with PCle Express 3 1
- Dimension (L x W x H): 22mm x 80mm x 2.2mm
- Weight: 7g
- Warranty: 3 Year
- Compliance CE, FCC, BSMI, C-Tick, VCCI, KCC, RRL, RoHS, China RoHS, WEEE, TUV, UL, IC, Marocco, SATA-IO, UKCA
- Power consumption 0.195W idle / 0.279W avg / 0.642W (MAX) read / 1.535W (MAX) write
- Nand Flash: 3D NAND

- Trim support
- Multistep data
- Device sleep support
- Operating temperature: : 0°C-70°C
- Storage temperature: -40°C-85°C
- O/S Supported: Windows® 7* / 8.0* / 8.1 / 10 / 11 (*May require

Illustrative images

- Shock resistence: 1,500G/0.5m/sec
- Vibration Operating: 5 gRMS, 10-200 Hz
- Vibration Non operating: 4,9 gRMS, 7-800 Hz
- Error correction: ECC

Warranty: 36 months

With immediate exchange offered directly by local supplier worldwide

INFORMATION PROVIDED IN THIS DOCUMENT PERTAIN TO K-MEMORY - PRODUCTS AND IS SUBJECT TO CHANGE AT ANY TIME